

# TestkingIT

Testking IT

> Contact Us Login / Register Search...

- HOME
- ALL VENDORS
- ★ GUARANTEE
- ? FAQ
- TESTIMONIALS
- CART (0)



Try **Desktop Test Engine** before you buy

We're not the only ones **happy** about TestKingsIT Practice Material ...

48236+ customers in 100+ countries use TestKingsIT Test Engine. Meet our customers.

- iMessenger
- VOREED
- GetCustom
- JET ORANGE
- iCompany
- Paradoxx



<http://www.testkingit.com/>

Latest practice material - Exam Cram - TestKingIT

**Exam :** 1Z0-861

**Title :** Java Enterprise Edition 5 Business  
Component Developer Certified  
Professional Upgrade Exam

**Vendors :** Oracle

**Version :** DEMO

NO.1 A developer maps the abstract entity class Account with concrete entity sub. classes CreditCardAccount and SavingsAccount using the single table per class hierarchy strategy. Which two

statements are true? (Choose two.)

- A. Instances of CreditCardAccount and SavingsAccount are stored in the same table.
- B. All columns that correspond to fields declared in Account must be defined as nullable in the database.
- C. The fields declared in Account are stored in a different table than the ones declared in CreditCardAccount and SavingsAccount.
- D. All columns that correspond to fields declared in CreditCardAccount or SavingsAccount must be defined as nullable in the database.

Answer: A,D

NO.2 The Java Persistence API defines the semantics of the remove operation and the entity lifecycle states.

Which statement is true when the remove method is invoked on an entity X?

- A. If X is a removed entity it becomes managed.
- B. If X is a new entity it will be removed from the database.
- C. The remove method is always cascaded to related entities.
- D. If X is a detached entity an IllegalArgumentException will be thrown.

Answer: D

NO.3 Your application uses the Java Persistence API to access a database. This application must reject

adding an instance to the database if it does NOT pass validation tests for values of two persistence

properties. The database contains some data that will NOT pass such validation. Only the new records

must be validated. Which option will achieve this behavior?

- A. Add validation logic to the setter methods for each property.
- B. Add the PrePersist callback method with all of the validation logic.
- C. Add the PostPersist callback method with all of the validation logic.
- D. Add PrePersist and PreUpdate callback methods with all of the validation logic.

Answer: B

NO.4 A developer wants to create a business interface for both local and remote usage. For

performance reasons the remote interface should NOT be called by a client in the same JVM. Which statement is required to accomplish this, assuming there is no deployment descriptor?

- A. The business methods are defined in one interface which must be annotated with both @Local and @Remote.
- B. The business methods are defined twice in one interface. One method is annotated with @Local and the other is annotated with @Remote.
- C. The business methods are defined in a common interface by two other interfaces which are annotated with @Local and @Remote respectively. The bean implements the super interface.
- D. The business methods are defined in a common interface. It is extended by two interfaces, annotated with @Local and .Remote respectively. Both interfaces are implemented by the bean class.

Answer: D

NO.5 Which statement about the combination of mapping defaults, annotations, and XML descriptors is correct?

- A. All mapping annotations must always be processed by the persistence provider.
- B. Some annotations, like the @Entity annotation, must always be processed by the persistence provider.
- C. The mapping information for an entity class specified by annotations and in XML descriptors must be distinct.
- D. If multiple entity listeners are defined, the order in which they are invoked can be defined or overwritten in the XML descriptor.

Answer: D

NO.6 A developer wants to create a Java Persistence query that will include a subquery. Which three are true? (Choose three.)

- A. Subqueries can be used in a FROM clause.
- B. Subqueries can be used in a WHERE clause.
- C. The ANY expression can be used only with a subquery.
- D. The EXISTS expression can be used only with a subquery
- E. The MEMBER expression can be used only with a subquery.

Answer: B,C,D

NO.7 Which two statements are true? (Choose two.)

- A. All types of enterprise beans can be transaction-aware
- B. Typically, finE. grained objects, such as an employee record, should be remotely accessible.
- C. The client view of any given enterprise bean will be consistent across all EJB 3.0 containers without the need to recompile the bean.
- D. As long as a given enterprise bean is NOT recompiled, its security attributes are guaranteed to be consistent across all EJB 3.0 containers in which it is deployed.

Answer: A,C

NO.8 A Java Persistence application uses entities mapped to tables from two datasources in the same transaction.

What statement is correct?

- A. This is NOT possible.
- B. The entities must be packaged into two persistence units.
- C. The entities can be packaged into a single persistence unit
- D. The entities must be packaged using two different persistence.xml files.

Answer: B

NO.9 A developer is creating an entity which is mapped to a table that has a primary key constraint defined on two character columns and would like to use mapping defaults as much as possible to simplify the code.

Which two mapping options can be chosen.? (Choose two.)

- A. Use an @Id property that constructs a private field as a concatenation of two columns.
- B. Use a separate class to map those two columns and use an @IdClass annotation to denote the primary key field or property in the entity.
- C. Use a separate @Embeddable class to map those two columns and use an @EmbeddedId annotation to denote a single primary key field or property in the entity.
- D. Use a separate @Embeddable class to map those two columns and add two fields or

properties to the entity, each marked as `@Id`, that correspond to the fields or properties in the embeddable class.

E. Use a separate class to map those two columns. Specify that class using `@IdClass` annotation on the entity class. Add two fields or properties to the entity, each marked as `@Id`, that correspond to the fields or properties in that separate class.

Answer: C,E

NO.10 A User entity is in a one-to-many relationship with a Book entity.

A developer writes a query to delete users that have a first name of 'Fred' or 'Ginger', and writes the

following Java Persistence query language statement:

```
DELETE FROM User u WHERE u.name IN ('Fred1', 'Ginger')
```

If the query fails with a `PersistenceException`, what can be the cause?

- A. The syntax of the query is NOT correct.
- B. The query causes a foreign key integrity constraint to be violated.
- C. The database does NOT have any users with the name 'Fred' or 'Ginger'.
- D. The entities corresponding to the users with the name 'Fred' or 'Ginger' are already being managed by the persistence context.

Answer: B

NO.11 A stateful session bean contains a number of instance variables. The types of instance variables A and

B are NOT serializable. Instance variable B is a complex type which is populated by many business calls,

and can, therefore, NOT be refilled by the client without starting all over. A helper instance variable C is

defined as having a `Serializable` type, and can hold all the information which is in variable B.

For example,

B is of type `XML-DOM Tree` and C of type `String`. Which two solutions, when combined, maintain the state

of the session bean over a passivation and activation by the container? (Choose two.)

- A. The value of helper variable C is used to create the value of instance variable B in the beans no-arg constructor.

- B. The value of helper variable C is used to create the value of instance variable B in a `@PostCreate` annotated method.
  - C. The value of helper variable C is used to create the value of instance variable B in a `@PostActivate` annotated method
  - D. Instance variable A must be made null and instance variable B must be converted to a `Serializable` type and assigned to another instance variable in a `@PreDestroy` annotated method.
  - E. Instance variable A must be defined `transient`. Instance variable B must be converted to a `Serializable` type, set to null, and assigned to the instance variable C in a `@PrePassivate` annotated method.
- Answer: C,E

NO.12 A developer writes an enterprise application and packages it into an `.ear` file. The application contains two persistence units defined at the `.ear` level with persistence unit names `FooPU` and `BarPU`. The application also contains an `ejB.jar` with one stateless session bean. Which code, when added to the stateless session bean class, injects an `EntityManagerFactory` at runtime?

- A. `@PersistenceUnit`  
`private EntityManagerFactory emf;`
- B. `@PersistenceContext`  
`private EntityManagerFactory emf;`
- C. `@PersistenceUnit(unitName="BarPU")`  
`private EntityManagerFactory emf;`
- D. `@Resource(name="BarPU",type=EntityManagerFactory.class)`  
`private EntityManagerFactory emf;`

Answer: C

NO.13 Within a Java EE environment, which annotation can be used to inject an entity manager factory?

- A. `@Entity`
- B. `@Factory`
- C. `@JTAFactory`
- D. `@PersistenceUnit`
- E. `@PersistenceContext`

Answer: D

NO.14 XYZ Software develops business components using both the EJB 2.1 and EJB 3.0 APIs. Some customers are reluctant to completely migrate to the EJB 3.0 model, but are willing to have EJB 2.1

session beans invoke EJB 3.0 session beans.

How should XYZ Software enhance these components to meet this customer requirement?

A. Use `@EJB` to inject a reference to the EJB 3.0 business interface into the EJB 2.1 bean class.

B. Use `<ejb.ref>` in `ejb.jar.xml` for the EJB 2.1 bean to declare a reference to the EJB 3.0 business interface.

C. Add an EJB 3.0-style business interface to EJB 2.1 beans to achieve interoperability between EJB 2.1 and EJB 3.0 beans.

D. Use `@RemoteHome` and `@LocalHome` to adapt EJB 3.0 beans so that EJB 2.1 beans can look up the adapted home interfaces using JNDI.

Answer: D

NO.15 An Application Assembler is given the following stateless session bean:

```
10. @Stateless public class MyBean implements MyInt {
11. @RolesAllowed("SECRET")
12. public void methodA(int x) {}
13. public void methodA(String y) {}
14. public void methodB(String z) {}
15.}
```

A deployment descriptor is also supplied, a portion of which reads as follows:

```
20. <method.permission>
21. <role.name>AGENT</role.name>
22. <method>
23. <ejb.name>MyBean</ejb.name>
24. <method.name>methodA</method.name>
25. </method>
26. </method.permission>
```

Which statement is true?

A. A client in any role will be able to access any of the methods.

B. A client in the role "AGENT" will be able to access any of the methods.

C. A client in the role "SECRET" will be able to access any of the methods.

D. A client in the role "AGENT" will be able to access `methodB` and `methodA(String)`, but not

methodA(int).

E. A client in the role "SECRET" will be able to access methodA(int) and methodB, but NOT methodA(String).

Answer: B

NO.16 A Java EE 5 application contains a session bean which uses a security role USER. A group called

people is defined in an LDAP server. Which two define appropriate EJB role responsibilities?

(Choose

two.)

A. The deployer defines and configures the LDAP realm.

B. The system administrator defines and configures the LDAP realm.

C. The deployer maps the application role USER to the LDAP group people

D. The system administrator maps the application role USER to the LDAP group people.

Answer: B,C

NO.17 The Java Persistent API defines certain rules for persistent entities. These rules are required by the

persistent provider to manage entities at runtime.

Which statement is correct, assuming NO mapping descriptor is used?

A. Entities must extend a persistent base class.

B. Entities must implement the interface PersistentEntity to be managed by the persistent provider.

C. A field without a transient modifier must be annotated as @Persistent to be stored in the database.

D. A field without a transient modifier must be annotated as @Transient to NOT be stored in the database.

Answer: D

NO.18 Which two are true about EJB 3.0 exception classes? (Choose two.)

A. The javax.ejb.NoSuchEJBException is an application exception.

B. The javax.ejb.EJBException extends java.lang.RuntimeException.

C. The javax.ejb.EJBTransactionRequiredException is an application exception. D. An application

exception must NOT be a subclass of java.rmi.RemoteException.

E. The javax.ejb.EJBTransactionRolledbackException is an application exception.

F. Any subclass of java.lang.RuntimeException is always considered a system exception.

Answer: B,D

NO.19 A developer writes two session beans which cooperate. The first session bean, ShoppingCart, collects orders and is implemented as a stateful session bean. The second session bean, CalculateDiscount, is implemented as a stateless session bean and runs on a different server. ShoppingCart contains the method getTotalPrice, which calculates the total price of the order in the ShoppingCart, including discounts. Discounts are calculated by CalculateDiscount using the information on the ShoppingCart bean, combined with data from a database. Which scenario can accomplish this?

A. The CalculateDiscount offers a method calculate which is invoked by the ShoppingCart bean passing the this reference.

B. The CalculateDiscount offers a method calculate which is invoked by the ShoppingCart bean.

CalculateDiscount accesses the ShoppingCart instance by JNDI lookup.

C. The CalculateDiscount offers a method calculate which is invoked by the ShoppingCart bean passing its reference obtained from the SessionContext.getBusinessObject method.

D. The CalculateDiscount offers a method calculate which is invoked by the ShoppingCart bean.

CalculateDiscount accesses the state of ShoppingCart by dependency injection.

Answer: C

NO.20 Bean Provider has been asked to write a stateless session bean, MyBean with a single method

breakout. A System Administrator guarantees that all clients accessing the bean will be identified by

mutual SSL authentication. The Bean Provider's task is to ensure that breakout always logs identity

information of the client that invoked it. Which solution would satisfy this requirement?

A. Access the identity information in the X.509 certificate used to authenticate the user from within breakout.

B. Use the getCallerPrincipal method on an injected SessionContext to determine the required

information.

C. Use the `isCallerInRole` method on an injected `SessionContext` to determine the required information.

D. Ensure that the breakout method is appropriately annotated with `@RolesAllowed`.

Answer: B