

TestkingIT

Testking IT

> Contact Us

Login / Register

Search...



HOME

ALL VENDORS

★ GUARANTEE

? FAQ

TESTIMONIALS

CART (0)



Try **Desktop Test Engine** before you buy

We're not the only ones **happy** about TestKingsIT Practice Material ...

48236+ customers in 100+ countries use TestKingsIT Test Engine. Meet our customers.



<http://www.testkingit.com/>

Latest practice material - Exam Cram - TestKingIT

Exam : SU0-224

Title : Huawei Certified Datacom
Professional - Fast Certification

Vendors : Huawei

Version : DEMO

NO.1 Which of the following character strings matches the regular expression 100\$?

- A. 3100
- B. 100
- C. 1008
- D. 100 200

Answer: B

NO.2 A Notification message with Error Code 2 indicates an error OPEN message. Which of the following error sub-codes can be contained in this OPEN message?

- A. 1: indicates that the version number is not supported.
- B. 2: indicates that the AS of the peer is incorrect.
- C. 3: indicates that the BGP identifier is incorrect.
- D. 4: indicates that the Optional Parameters filed is not supported.

Answer: ABCD

NO.3 TRUE/FALSE: An IP-prefix-filter is used to filter IP prefixes and data packets.

- A. True
- B. False

Answer: B

NO.4 What is the function of the peer ignore command?

- A. Deletes a BGP peer.
- B. Retains all configurations of the peer, and maintains the BGP peer relationship with the peer, but does not receive the routes sent from the peer.
- C. Retains all configurations of the peer, and maintains the BGP peer relationship with the peer, but does not advertise routes to the peer.
- D. Retains all configurations of the peer, interrupts the BGP peer relationship with the peer, and clears all related routing information.

Answer: D

NO.5 Besides an IPv4 address, a router distinguisher (RD) also contains a flag that distinguishes IP routes to the same destination IP address in different VPNs.

How many bits are there in the flag?

- A. 16

- B. 32
- C. 64
- D. 128

Answer: C

NO.6 Which statement about the trunk interface is true?

- A. A trunk interface is always connected to hosts.
- B. Multiple VLAN IDs can be set on a trunk interface. The VLAN IDs can be the same as or different from the PVID.
- C. The trunk interface cannot have a PVID.
- D. If the trunk interface receives a packet with a VLAN not in the allowed VLAN list, the trunk interface broadcast the packet in the VLAN.

Answer: B

NO.7 Which statements about OSPF packets are true?

- A. Hello packets can be sent after OSPF is enabled on an interface.
- B. LS Request packets are sent only after an adjacency is established.
- C. LS Update packets contain detailed LSA information for LSDB synchronization.
- D. LS Update packets are sent only after an adjacency is established.

Answer: ABC

NO.8 Which of the attributes must exist in the BGP Update messages ?

- A. LOCAL_PREF
- B. NEXT_HOP
- C. ORIGIN
- D. AS PATH

Answer: BCD

NO.9 Which of the following are factors that affect QoS?

- A. Bandwidth
- B. Delay
- C. Jitter
- D. Loss of packet

Answer: ABCD

NO.10 TRUE/FALSE: A device can be assigned an IP address 192.168.13.175, with the

mask being 255. 255.

255. 240.

A. True

B. False

Answer: B

NO.11 In OSPF, which of the following statements are incorrect regarding Router LSA generated by Router A.?

A. In Point-to-Point link type, Data is set to the interface IP address of RouterA.

B. In TransNet link type, Data is set to the interface IP address of RouterA.

C. In StubNet link type, Data is set to the interface IP address of RouterA.

D. In Virtual link type, Data is set to the Router ID of RouterA.

Answer: CD

NO.12 What is the maximum bits of a Class C address can be used for subnet?

A.6

B.8

C.12

D.14

Answer: A

NO.13 Which following BGP attribute can used to define a set of prefixes with the same characteristics?

A. Origin

B. Nexthop

C. Community

D. MED

Answer: C

NO.14 TRUE/FALSE: Only Router-LSAs and Network-LSAs are involved in intra-area route calculations.

A. True

B. False

Answer: A

NO.15 In IPv4, which of the following is the SSM address range allocated by the IANA?

A. 232. 0. 0. 0/24

B. 225. 0. 0. 0/8

C. 232. 0. 0. 0/8

D. 239. 0. 0. 0/8

Answer: D

NO.16 TRUE/FALSE: Only one BGP process can be configured on a router.

A. True

B. False

Answer: A

NO.17 Which of the following configurations can be performed to implement fast failure detection on a network?

A. Reduce the holdtime of Join/Prune messages.

B. Reduce the interval for an interface to send Hello messages.

C. Set up a PIM BFD session between network segment neighbors.

D. Reduce the interval for sending Join/Prune messages.

Answer: BC

NO.18 Which are the functions of the route target on an MPLS VPN network?

A. Enable the peer PE to determine whichVPNv4 routes can be imported to the specified VRF.

B. Enable the peer PE to determine whichVPNv4 routes cannot be imported to the specified VRF.

C. Enable the peer CE to determine whichVPNv4 routes can be imported to the specified VRF.

D. Enable the peer CE to determine whichVPNv4 routes cannot be imported to the specified VRF.

Answer: AB

NO.19 Which of the following as-path attributes match this AS-path-filter?

ip AS-path-filter 1 permit 100\$|400\$

A. 100

B. 3100

C. 1234 1400

D. 300 400

Answer: ABCD

NO.20 Which of the following technologies can reduce the scale of broadcast domain?

- A. VLAN
- B. Trunk
- C. RARP
- D. STP

Answer: A